

Jumper Cables



1/2" Superflexible Foam Dielectric Cable



PRODUCT FEATURES

- No need for tape or other external weatherproofing
- IP68-classified and water-pressure proof tested down to 25 m
- Designed to maintain high pressure on contact surfaces to reduce intermodulation
- Each cable individually tested
- 10-year comprehensive warranty

COMMON FOR ALL	
CABLE TYPE	1/2" Superflex
FREQUENCY RANGE	0 - 5 GHz
VSWR / RETURN LOSS	
0 - 2.7 GHz	1.12 / -25 dB*
INTERMODULATION**	
2 x 20 W transmitter	< -160 dBc
OPERATING TEMPERATURE	-55 °C to +80 °C

DIN 7/16 TO DIN 7/16	
ARTICLE	CONNECTORS
JBB0-S012-ACxx***	DIN 7/16 male to DIN 7/16 male
JAB0-S012-ACxx	DIN 7/16 female to DIN 7/16 male

DIN 7/16 TO N	
ARTICLE	CONNECTORS
JBD0-S012-ACxx	DIN 7/16 male to N male
JBC0-S012-ACxx	DIN 7/16 male to N female

N TO N	
ARTICLE	CONNECTORS
JDD0-S012-ACxx	N male to N male
JCC0-S012-ACxx	N female to N female

* Typical performance for jumpers of ordinary length.

** During intermodulation measurement, cables were exposed to shock and vibration.

*** XX is the length of the cable. For example: AC05=0.5 m, AC10=1.0 m.