

Connectors

1/2" Foam Dielectric - Contact Springs



PRODUCT FEATURES

- Reusable
- Auto-flaring for faster installation
- 10-year comprehensive warranty
- No need for tape or other external weatherproofing
- IP68-classified and water-pressure proof tested down to 25 m
- High quality O-rings on outer conductor and cable jacket ensure functional integrity even after accidental damage to cable jacket
- Designed to maintain high pre sure on contact surfaces to reduce intermodulation

COMMON FOR ALL	
CABLE FORMAT	1/2"
CONNECTOR OPERATING FREQUENCY	0 - 7500 MHz
VSWR / RETURN LOSS	
0 - 2000 MHz	1.036 / -35 dB
0 - 2500 MHz	1.065 / -30 dB
CABLE COMPATIBILITY	Andrew LDF4-50 NK Cables RFA 1/2"-50 Cellflex LCF 1/2" Cu2Y RFS LCF 1/2"-50 Cu2Y Cablewave FLC 12 Eupen 5128 Acome HPL 50-1/2" flex Leoni FlexLine 1/2" R Condumex RF 1/2"-50
INTERMODULATION*	
2 x 20 W transmitter	< -156 dBc
CONNECTING TIME	2 - 3 min
WEIGHT	190 g (0.42 lb)
OPERATING TEMP.	-55 °C to +80 °C
PIECES IN BOX	25
TOOL-KIT	CONK-F012-H0 (std.) CONK-F012-F0 (basic)



00NM-F012-H1

00NF-F012-H1



716M-F012-H1

716F-F012-H1

ARTICLE	00NM-F012-H1	00NF-F012-H1	716M-F012-H1	716F-F012-H1
CONNECTOR	N male	N female	DIN 7/16 male	DIN 7/16 female
DIAMETER	27 mm (1.06 in) NM	27 mm (1.06 in) NF	34 mm (1.34 in) 7/16m	29 mm (1.14 in) 7/16f
LENGTH	68 mm (2.68 in) NM	66 mm (2.60 in) NF	57 mm (2.25 in) 7/16m	55 mm (2.17 in) 7/16f

* During intermodulation measurement attached cables are exposed to shock and vibration.