

Connectors

7/8" Radiating Antenna Cable



PRODUCT FEATURES

- No need for tape or other external weatherproofing
- IP68-classified and water-pressure proof tested down to 25 m
- High quality O-rings on outer conductor and cable jacket ensure functional integrity even after accidental damage to cable jacket
- Designed to maintain high pressure on contact surfaces to reduce intermodulation
- Auto-flaring for faster installation
- Reusable
- 10-year comprehensive warranty

COMMON FOR BOTH

CONNECTOR OPERATING FREQUENCY	0 - 7.5 GHz
VSWR / RETURN LOSS	
0 - 2 GHz	1.036 / -35 dB
0 - 2.5 GHz	1.065 / -30 dB
CABLE COMPATIBILITY	NK Cables RFXT 7/8"-50
INTERMODULATION*	
2 x 20 W transmitter	< -156 dBc
CONNECTING TIME	4 - 5 min
WEIGHT	530 g (1.17 lb)
DIAMETER	43.5 mm (1.71 in)
LENGTH	85 mm (3.34 in)
OPERATING TEMP.	-55 °C to +80 °C
PIECES IN BOX	25
TOOL KIT	CONK-L078-A0



716m-L078-A0



716f-L078-A0

ARTICLE	716m-L078-A0	716f-L078-A0
CONNECTOR	DIN 7/16 male	DIN 7/16 female

* During intermodulation measurement attached cables are exposed to shock and vibration.