

Connectors

1/2" Flexible Foam Dielectric



PRODUCT FEATURES


- Reusable
- Auto-flaring for faster installation
- 10-year comprehensive warranty
- IP68-classified and water-pressure proof tested down to 25 m
- High quality O-rings on outer conductor and cable jacket ensure functional integrity even after accidental damage to cable jacket
- Designed to maintain high pressure on contact surfaces to reduce intermodulation

COMMON FOR ALL	
CABLE FORMAT	1/2"
CONNECTOR OPERATING FREQUENCY	0 - 7500 MHz
VSWR / RETURN LOSS	
0 - 2000 MHz	1.036 / -35 dB
0 - 2500 MHz	1.065 / -30 dB
CABLE COMPATIBILITY	Acome HPL 50-1/2 SF Andrew FSJ4-50B Cablewave S-FLC 12 Condumex RF 1/2"-50 SF Eupen 5092 1/2" Hiflex Leoni FlexLine 1/2" S NK Cables RFF 1/2"-50 RFS Cellflex SCF12-50J
INTERMODULATION*	
2 x 20 W transmitter	< -156 dBc
CONNECTING TIME	5 - 6 min
WEIGHT	190 g (0.42 lb)
DIAMETER	27 mm (1.06 in)
LENGTH	76 mm (2.99 in)
OPERATING TEMP	-55 °C to +80 °C
PIECES IN BOX	25
TOOL KIT	CONK-S012-B0



NM-S012-A0

NF-S012-A0



716M-S012-A0

716F-S012-A0

ARTICLE	NM-S012-A0	NF-S012-A0	716M-S012-A0	716F-S012-A0
CONNECTOR	N male	N female	DIN 7/16 male	DIN 7/16 female

* During intermodulation measurement attached cables are exposed to shock and vibration.