

RF Adapters

7/16 DIN and N



PRODUCT PROFILE

Exir Telecom's RF Adapters are developed for digital cellular applications such as GSM, TETRA, 3G and CDMA systems. These adapters are developed to be used in combination with our RF connectors for optimal performance level.

Exir Telecom RF adapters are designed to operate under harsh climatic conditions with excellent overall performance. The silver-plating ensures the finest protection against any kind of corrosion.

The RF Adapters are available in all 7/16 DIN and N - male and female combinations.

GENERAL SPECIFICATION	
FREQUENCY RANGE	0.05 - 7500 MHz
IMPEDANCE	50 Ohm
VSWR / RETURN LOSS	1.04 / -34 dB
INTERMODULATION	
2x20 W transmitter	-165 dBc
OPERATING TEMPERATURE	-40 °C to +85 °C, -40 °C to +185 °F
SEALING	Passed the IPX8 test
PLATING	Silver-plated

ARTICLE	NO
7/16M-7/16M AG/AG	018-230000
7/16M-7/16F AG/AG	018-230010
7/16M-NM/50 AG/AG	018-230020
7/16M-NF/50 AG/AG	018-230030
7/16F-7/16F AG/AG	018-230040
7/16F-NF/50 AG/AG	018-230050
NM/50-7/16F AG/AG	018-230060
NM/50-NM/50 AG/AG	018-230070
NM/50-NF/50 AG/AG	018-230080
NF/50-NF/50 AG/AG	018-230090