

# External Grounding Kits

## Lightning Protection for Connectors

### PRODUCT FEATURES

- Fast and easy installation
- Large contact surface area
- IP68-classified and water-pressure proof tested down to 25 m
- No need for tape or other external weatherproofing
- Made of silver-plated brass and stainless steel
- Non-corrosive
- Reusable
- 10-year comprehensive warranty



### PRODUCT PROFILE

The external grounding kit is designed to be mounted around the connector and to cause the connector itself to function as a grounding device.

This solution is very easy to install and provides extra protection at the feeder connector.



ARTICLE	EXGR-F012-AA00	EXGR-F078-AA00	EXGR-F114-AA00	EXGR-F158-AA00
<b>CONNECTOR</b>	xxxx-F012-G1	xxxx-F078-AE02	xxxx-F114-AD00	xxxx-F158-AD00
<b>COMPATIBILITY</b>	xxxx-F012-H1	xxxx-F078-AF00 xxxx-F078-AG00		
<b>CONTACT AREA</b>	>25 mm <sup>2</sup> (0.04 in <sup>2</sup> )	>25 mm <sup>2</sup> (0.04 in <sup>2</sup> )	>25 mm <sup>2</sup> (0.04 in <sup>2</sup> )	>25 mm <sup>2</sup> (0.04 in <sup>2</sup> )
<b>CABLE LENGTH</b>	600 mm (23.64 in)	600 mm (23.64 in)	600 mm (23.64 in)	600 mm (23.64 in)
<b>OPERATING TEMP.</b>	-55 °C to +80 °C	-55 °C to +80 °C	-55 °C to +80 °C	-55 °C to +80 °C
<b>PIECES IN BOX</b>	50	50	50	50