

External Grounding Kits

Lightning Protection for Connectors



PRODUCT FEATURES

- Reusable
- Non-corrosive
- Fast and easy installation
- Large contact surface area
- 10-year comprehensive warranty
- Made of silver-plated brass and stainless steel
- No need for tape or other external weatherproofing
- IP68-classified and water-pressure proof tested down to 25 m

PRODUCT PROFILE

The external grounding kit is designed to be mounted around the connector and to cause the connector itself to function as a grounding device.

This solution is very easy to install and provides extra protection at the feeder connector.



ARTICLE	EXGR-F012-AA00	EXGR-F078-AA00	EXGR-F114-AA00	EXGR-F158-AA00
CONNECTOR	xxx-F012-G1	xxx-F078-AE02	xxx-F114-AD00	xxx-F158-AD00
COMPATIBILITY	xxx-F012-H1	xxx-F078-AF00 xxx-F078-AG00		
CONTACT AREA	>25 mm ² (0.04 in ²)	>25 mm ² (0.04 in ²)	>25 mm ² (0.04 in ²)	>25 mm ² (0.04 in ²)
CABLE LENGTH	600 mm (23.64 in)	600 mm (23.64 in)	600 mm (23.64 in)	600 mm (23.64 in)
OPERATING TEMP	-55 °C to +80 °C	-55 °C to +80 °C	-55 °C to +80 °C	-55 °C to +80 °C
PIECES IN BOX	50	50	50	50