

Grounding Kits

Lightning Protection for Foam Dielectric Cables

PRODUCT FEATURES

- Reusable
- Fast and easy installation
- Large contact surface area
- Fits multiple cable brands
- 10-year comprehensive warranty
- No need for tape or other external weatherproofing
- IP68-classified and water-pressure proof tested down to 25 m



PRODUCT PROFILE

Grounding kits from Exir Telecom feature an efficient design enabling multiple units to be mounted very close together. A simple, adjustable construction allows for easy attachment to a wide range of cables from various manufacturers. These grounding kits are reusable and 100% weatherproof without the need for tape or any other external weatherproofing.

The contact surfaces are designed to closely fit the corrugated surface of the outer conductor, thus avoiding unnecessary pressure. As a result, the effect of grounding on the VSWR measurement of the antenna line is barely detectable.



ARTICLE	GROU-F012-AB00	GROU-F078-AB00	GROU-F114-AB00	GROU-F158-AB00
CABLE COMPATIBILITY	Andrew LDF4-50 NK Cables RFA 1/2"-50 Cellflex LCF 1/2" Cu2Y RFS LCF 1/2"-50 Cu2Y Cablewave FLC 12 Eupen 5128 Acome HPL 50-1/2" flex Leoni FlexLine 1/2" R Condumex RF 1/2"-50	Acome HPL 50-7/8" flex Acome HPL 50-7/8" LA Acome M5423 7/8 UP Andrew AVA5-50 Andrew LDF5-50A Cablewave FLC 78 Cellflex LCF 7/8" Cu2Y Cellflex LCF78-50JA Condumex RF 7/8"-50 Eupen 5228 Eupen 5228A EC5-50A Leoni FlexLine 7/8" R NK Cables RF 7/8"-50 NK RFA 7/8" Tsvelit PK50-22-39-C 7/8"R HANSEN 7/8"	Acome HPL 50-1 1/4 flex Andrew LDF6-50 Cablewave FLC 114 Cellflex LCF 1 1/4" Cu2Y Condumex RF 1 1/4"-50 Eupen 5328 Eupen Hiflex EC6-50-HF Leoni FlexLine 1 1/4" R NK Cables RFA 1 1/4"-50 RFS LCFS114-50JA	Acome HPL 50-158 flex Andrew AVA7-50 Andrew LDF7-50A Cablewave FLC 158 Cellflex LCF 1 5/8" Cu2Y Condumex RF 1 5/8"-50 Leoni FlexLine 1 5/8" R NK Cables RFA 1 5/8"-50 RFS LCF158-50JA
GROUND CONN.	Cable clip, M5	Cable clip, M5	Cable clip, M5	Cable clip, M5
DIMENSIONS	50 x 25 x 32 mm	50 x 32 x 43 mm	50 x 43 x 57 mm	52 x 54 x 68 mm
H x W x D (front view)	(1.97 x 0.98 x 1.26 in)	(1.97 x 1.26 x 1.69 in)	(1.97 x 1.69 x 2.24 in)	(2.05 x 2.13 x 2.68 in)
CONTACT AREA	>25 mm ² (0.04 in ²)	>25 mm ² (0.04 in ²)	>25 mm ² (0.04 in ²)	>25 mm ² (0.04 in ²)
WEIGHT	242 g (0.53 lb)	306 g (0.66 lb)	424 g (0.94 lb)	556 g (1.23 lb)
CABLE LENGTH	600 mm (23.64 in)	600 mm (23.64 in)	600 mm (23.64 in)	600 mm (23.64 in)
OPERATING TEMP.	-55 °C to +80 °C	-55 °C to +80 °C	-55 °C to +80 °C	-55 °C to +80 °C

TOOL KITS	CPKI-0000-C0	CPKI-0000-C0	CPKI-0000-C0	CPKI-0000-C0
-----------	--------------	--------------	--------------	--------------