

Jumper Cables

1/2" Foam Dielectric Cable



PRODUCT FEATURES

- 10-year comprehensive warranty
- No need for tape or other external weatherproofing
- IP68-classified and water-pressure proof tested down to 25 m
- Designed to maintain high pressure on contact surfaces to reduce intermodulation
- Each cable individually tested and labelled with return loss graph, 0 - 2200 MHz

COMMON FOR ALL

CABLE TYPE	1/2"
FREQUENCY RANGE	0 - 5000 MHz
VSWR / RETURN LOSS	
0 - 1000 MHz	1.08 / -28 dB (-35 dB)*
1000 - 2200 MHz	1.10 / -26 dB (-35 dB)*
INTERMODULATION**	
2 x 20 W transmitter	< -156 dBc
OPERATING TEMPERATURE	-55 °C to +80 °C

DIN 7/16 TO DIN 7/16

ARTICLE	CONNECTORS
JBB0-F012-ABxx***	DIN 7/16 male to DIN 7/16 male
JAB0-F012-ABxx	DIN 7/16 female to DIN 7/16 male

DIN 7/16 TO N

ARTICLE	CONNECTORS
JBD0-F012-ABxx	DIN 7/16 male to N male
JAD0-F012-ABxx	DIN 7/16 female to N male

N TO N

ARTICLE	CONNECTORS
JDD0-F012-ABxx	N male to N male
JCD0-F012-ABxx	N female to N male

* Typical return loss connector.

** During intermodulation measurement attached cables are exposed to shock and vibration.

*** XX is the length of the cable. For example: AB05=0.5 m, AB10=1.0 m.