

2-Way Power Splitter

790 - 2700 MHz



PRODUCT FEATURES

- Made from silver-plated brass
- 10-year comprehensive warranty
- No need for tape or other external weatherproofing
- IP68-classified and water-pressure proof tested down to 25 m

ARTICLE	AT2G-716F-AB00	AT2G-00NF-AB00
FREQUENCY RANGE	790 - 2700 MHz	790 - 2700 MHz
INPUT POWER		
790 - 960 MHz	1000 W	300 W
1700 - 2200 MHz	700 W	150 W
2500 - 2700 MHz	500 W	100 W
CONNECTORS	DIN 7/16 female	N female
INPUTS/OUTPUTS	1/2	1/2
VSWR / RETURN LOSS	1.17 / -22 dB	1.17 / -22 dB
INSERTION LOSS	<0.05 dB	<0.05 dB
INTERMODULATION		
2 x 20 W transmitter	< -156 dBc	< -156 dBc
IMPEDANCE	50 ohm	50 ohm
WEIGHT	500 g (1.1 lb)	500 g (1.1 lb)
OPERATING TEMPERATURE	55 °C to +80 °C	55 °C to +80 °C
DIMENSIONS		
H x W x D	225 x 84 x 28 mm (8.85 x 3.30 x 1.10 in)	240 x 92 x 28 mm (9.44 x 3.62 x 1.10 in)
PIECES IN BOX	10	10

