

# Power Splitters

3300 - 3600 MHz



## PRODUCT FEATURES

- Good VSWR
- Made of silver-plated brass
- EPDM O-rings eliminate water intrusion
- 10-year comprehensive warranty
- No need for tape or other external weatherproofing
- IP68-classified and water-pressure proof tested down to 25 m

ARTICLE	AT2T-00NF-AA00	AT2T-716F-AA00
<b>FREQUENCY RANGE</b>	3300 - 3500 MHz	3300 - 3500 MHz
<b>INPUT POWER</b>	100 W	500 W
<b>CONNECTORS</b>	N female	7/16 female
<b>INPUTS/OUTPUTS</b>	1/2	1/2
<b>VSWR / RETURN LOSS</b>	1.12 / -25 dB	1.12 / -25 dB
<b>INSERTION LOSS</b>	0.05 dB	0.05 dB
<b>INTERMODULATION*</b>		
2 x 20 W transmitter	< -156 dBc	< -156 dBc
<b>IMPEDANCE</b>	50 ohm	50 ohm
<b>WEIGHT</b>	800 g (1.75 lb)	800 g (1.75 lb)
<b>OPERATING TEMPERATURE</b>	-55 °C to +80 °C	-55 °C to +80 °C
<b>DIMENSIONS</b>		
H x W x D	120 x 110 x 32 mm (4.73 x 4.33 x 1.26 in)	100 x 100 x 32 mm (3.94 x 3.94 x 1.26 in)

\* During intermodulation measurement attached cables are exposed to shock and vibration.