

3-Way Power Splitter

790 - 2700 MHz



PRODUCT FEATURES

- Made from silver-plated brass
- 10-year comprehensive warranty
- No need for tape or other external weatherproofing
- IP68-classified and water-pressure proof tested down to 25 m

ARTICLE	AT3G-716F-AB00	AT3G-00NF-AB00
FREQUENCY RANGE	790 - 2700 MHz	790 - 2700 MHz
INPUT POWER		
790 - 960 MHz	1000 W	300 W
1700 - 2200 MHz	700 W	150 W
2500 - 2700 MHz	500 W	100 W
CONNECTORS	DIN 7/16 female	N female
INPUTS/OUTPUTS	1/3	1/3
VSWR / RETURN LOSS	1.17 / -22 dB	1.17 / -22 dB
INSERTION LOSS	<0.05 dB	<0.05 dB
INTERMODULATION		
2 x 20 W transmitter	< -156 dBc	< -156 dBc
IMPEDANCE	50 ohm	50 ohm
WEIGHT	500 g (1.1 lb)	500 g (1.1 lb)
OPERATING TEMPERATURE	55 °C to +80 °C	55 °C to +80 °C
DIMENSIONS		
H x W x D	235 x 90 x 68 mm (9.3 x 3.6 x 2.7 in)	245 x 111 x 78 mm (9.7 x 4.4 x 3.1 in)
PIECES IN BOX	10	10

