

PDU

(Power Distribution Unit)



PRODUCT FEATURES

- Individual channel alarms
- Individual channel LED monitor

ARTICLE	EXT-30201	EXT-30202
ELECTRICAL		
INPUT VOLTAGE	20 - 60 V DC, positive or negative	20 - 60 V DC, positive or negative
INPUT POLARITY PROTECTION	Yes	Yes
OUTPUT VOLTAGE	12 V DC	12 V DC
OUTPUT PROTECTION	Over current and over voltage	Over current and over voltage
NUMBER OF SUPPORTED TMA PORTS	6	2
ALARM	Three pin alarm with NC and NO contacts individual LED indicator	Three pin alarm with NC and NO contacts individual LED indicator
ENVIRONMENTAL AND STANDARDS		
TEMPERATURE	-10 to +65 °C	-10 to +65 °C
EMC	EN 301 498-8	EN 301 498-8
ENVIRONMENTAL	EN 300 019	EN 300 019
SAFETY	EN 60 590	EN 60 590
INGRESS PROTECTION	IP20	IP20
MECHANICAL		
DIMENSIONS, WALL MOUNT		
(W x H x D)	218 x 125 x 43.5 mm	218 x 125 x 43.5 mm
1U 19" RACK MOUNT OPTIONAL		
WEIGHT	500 g	500 g
CONNECTORS	CIN 6 x SMB Male DC Molex Microfit 2 x 2 Alarm Molex Microfit 1 x 3	CIN 6 x SMB Male DC Molex Microfit 2 x 2 Alarm Molex Microfit 1 x 3